

# Plastocrete® -N

## Waterproofing Concrete Admixture

<b>Product Description</b>	A Concrete admixture in liquid form that acts both as a highly efficient plasticizer and a waterproofing agent. It complies with ASTM C 494-81 type A.	
<b>Uses</b>	Plastocrete® -N is recommended for use in structural and mass concrete, particularly water-retaining structures such as: ■ Reservoirs and dams. ■ Sewage works. ■ Canals. ■ Culvert tunnels And whenever waterproof concrete is required.	
<b>Advantages</b>	Plastocrete® -N provides the following properties: ■ Improved workability without increased water content. ■ Allows easier compaction leading to denser concrete and superior finish. ■ Increased strength and durability. ■ Reduced shrinkage. ■ Improved water tightness. ■ Chloride free-does not attack reinforcement.	
<b>Technical Data</b>		
<b>Type</b>	Liquid Modified Lignosulphonate.	Powder Modified Lignosulphonate.
<b>Colour</b>	Brown liquid	Brown liquid
<b>Density (at 20°C)</b>	1.08 kg/l	-
<b>Bulk density</b>	-	0.9 kg/l.
<b>Packaging</b>	5 and 20 kg pails 220 kg drums Available in tank packaging upon request.	25 kg bags
<b>Storage</b>	Store free from frost	Store in dry conditions.
<b>Shelf life</b>	18 months from date of production if stored properly in original unopened packing.	
<b>Application</b>		
<b>Dosage</b>	0.5% by weight of cement. Plastocrete® -N is compatible with all types of Portland Cement including S.R.C.	
<b>Dispensing</b>	Plastocrete® -N Liquid should be dispensed into the mixing water, prior to its addition to the aggregates. Plastocrete® -N Powder is added directly to the dry mixed aggregates. When overdosing accidentally occurs, apart from retardation of the initial set no detrimental effect will take place.	
<b>Safety Instructions</b>		
<b>Ecology</b>	Do not dispose of into water or soil but according to local regulations.	
<b>Transport</b>	Non-hazardous.	
<b>Safety Precautions</b>	Accidental splashes to the skin must be washed off with water and soap. Accidental splashes to the eyes or mucous membrane must be rinsed with clean warm water. Seek medical attention without delay.	
<b>Toxicity</b>	Non-Toxic under relevant Swiss health and safety codes.	



## Legal notes

The information and in particular the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the technical data sheet for the product concerned, copies of which will be supplied on request.

For further technical information, please consult our technical service department.



**Sika Egypt for Construction Chemicals**  
El Abour City  
1<sup>st</sup> industrial zone (A)  
Section # 10 Block 13035,  
Egypt

Tel : +202- 6100714/15/16/17/18  
Fax : +202- 6100759  
Mob : +2012- 3908822/55  
[www.sika.com.eg](http://www.sika.com.eg)

