
Sikalite[®]


Waterproofing Mortar Admixture

Product	A ready to use waterproofing admixture for cement : sand mortars in powder form.
Description	
Uses	Sikalite [®] is used in waterproof cement : sand renders for walls, facades, floor toppings and jointing mortars.
Advantages	Sikalite contains pore sealing and water-repelling substances which provide the following beneficial properties:
	Improved workability without increased water.
	 Increased impermeability. Chloride free.
	Chloride free.
Product Data	
Form	Hydrophobic powder.
Colour	Beige.
Packaging	20 x 1 kg bags/carton.
Storage	Store in dry conditions. Unaffected by frost.
Shelf life	12 months from date of production if stored properly in original unopened packing.
Technical Data	·
Density	$0.9 \pm 0.1 \text{ kg/l}.$
Compressive strength	Testing conditions:
-	Mortar 1: 6 (PC Jura Widegg and normal sand)
	Storage: + 20°C / R.H. 65%.

Tested on mortar prisms 4/ 4 /16 cm



Water consistent according to DIN



Testing period in hrs.



Application	
Consumption	2% by weight of cement.
Dispensing	Sikalite is added to the dry mixed cement: sand prior to the addition of water.
Safety Instructions	
Ecology	Do not dispose of into water or soil but according to local regulations
Transport	Non-hazardous.
Safety Precautions	Avoid dust development during application.
Toxicity	Non-toxic under the relevant, health and safety codes.
Legal notes	The information and in particular the recommendations relating to the application and end-use of Sika
	products, are given in good faith based on Sika's current knowledge and experience of products when properly stored, handled and applied under normal conditions. In practice, the differences in materials,

The information and in particular the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the technical data sheet for the product concerned, copies of which will be supplied on request.

For further technical information, please consult our technical service department.



Sika Egypt for Construction Chemicals El Abour City 1st industrial zone (A) Section # 10 Block 13035, Egypt

Tel :+202-6100714/15/16/17/18 Fax :+202-6100759

Mob :+2012- 3908822/55 www.sika.com.eg



